

Description & Features

- Aluminum alloy 6063 boy with heat dissipation.
- High quality and high efficiency Guide Lighting Plate.
- Super Long life designed drivers, MTBF estimated at 60,000 hours, LED works more stable.
- Protection class: Class 2.
- High quality LED chips with LM80.
- Lumens efficiency more than 80lm/w for fixture, CRI>80Ra.
- No bad glare and stroboscopic, no flicker.
- Power factor greater than 0.95.
- Triac, 1-10V, PWN, DALI dimming available.
- Long life, L70>50,000 Hours.
- Professional technology support, can offer Dialux solution, IES.

Certificate

- TUV-GS (No.:S50282495), ERP, CE, RoHs

Specifications

Model No.:	3030-18A	3030-24A
Power Consumption:	18W	24W
Input Voltage:	100-240V	100-240V
Operate Frequency:	50-60Hz	50-60Hz
Lumens Output:	1450-1650lm	19200-2200lm
LED Q'ty:	96pcs	96pcs
LED Brand	Epistar SMD2835	
Color Temperature:	3000K, 4000K, 5000K, 6000K	
CRI:	>80	
Beam Angle:	120°	
IP Rated:	IP40	
Power Factor:	>0.95	
Total Harmonic Distortion:	<20%	
Working Temp.:	-20°C ~ 40°C	
Storage Temp.:	-40°C ~ 70°C	
Lifespan L70(H):	>50,000 Hours	
Cable:	1.0m two-core high quality silicon wire	
Drivers:	External	
Fixture Weight:	1.4kg	

Note1: Different color LED light performance somewhat deviation, rate ≤ 5%

