



# LED Downlight



## Electrical Specifications


Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	5W
Power Factor	>0.9

## Light Output Specifications

Light source	10pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	470lm (6000K) 440lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming




## Dimensions



## Dimensions



Size	D96*H55mm
IP Rating	IP44
Weight	300g

## Installation



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications


Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	7W
Power Factor	>0.9

## Light Output Specifications

Light source	14 pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	660lm (6000K) 610lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming



## Dimensions



## Dimensions

Size	D130*H66mm
IP Rating	IP44
Weight	500g



## Installation

Cut hole:



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications

Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	9W
Power Factor	>0.9

## Light Output Specifications


Light source	18pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	850lm (6000K) 770lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming



## Dimensions


Size	D130*H66mm
IP Rating	IP44
Weight	500g

## Dimensions





## Installation

Cut hole:



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications


Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	15W
Power Factor	>0.9

## Light Output Specifications

Light source	30pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	1400lm (6000K) 1200lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming



## Dimensions




## Dimensions

Size	D160*H75mm
IP Rating	IP44
Weight	700g



## Installation

Cut hole:



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications

Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	9W
Power Factor	>0.9

## Light Output Specifications


Light source	18pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	850lm (6000K) 770lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming




## Dimensions

Size	D130*H66mm
IP Rating	IP44
Weight	500g

## Dimensions





## Installation



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications

Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	18W
Power Factor	>0.9

## Light Output Specifications


Light source	36pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	1700lm (6000K) 1500lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming



## Dimensions


Size	D180*H75mm
IP Rating	IP44
Weight	1000g

## Dimensions





## Installation

Cut hole:



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt







# LED Downlight



## Electrical Specifications

Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	20W
Power Factor	>0.9

## Light Output Specifications


Light source	40pcs 5630 SMD LED
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	1800lm (6000K) 1700lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming




## Dimensions

Size	D180*H75mm
IP Rating	IP44
Weight	1000g

## Dimensions





## Installation



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt





# LED Downlight



## Electrical Specifications

Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	24W
Power Factor	>0.9

## Light Output Specifications


Light source	48pcs Epistar SMD2835
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	283 2200lm (6000K ) 2000lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming




## Dimensions

Size	D230*H85mm
IP Rating	IP44
Weight	1300g

## Dimensions





## Installation



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt







# LED Downlight



## Electrical Specifications


Connection	Wire
Input Voltage	AC 90 - 260V
Total Power Usage	28W
Power Factor	>0.9

## Light Output Specifications

Light source	60pcs Epistar SMD2835
Brightness Degradation	< 1% per 1000 hours
Colour Rendering Index	>80
Light Purity	No UV or IR Radiation
Light Output	2500lm (6000K) 2200lm (3000K)
Viewing Angle	120°
Dimmable	Non dimmable/triac dimming




## Dimensions



## Dimensions

Size	D230*H85mm
IP Rating	IP44
Weight	1300g

## Installation



## Equivalent power guide

LED Model	CFL Equivalent
5 Watt	15 Watt
9 Watt	25 Watt
18 Watt	40 Watt

